



**QUICK-FIT**



**THE WORLD'S FASTEST DUCTING**


**HOSE ADAPTER**

Ø	PART NO.	APPROX. LENGTH	GAUGE	WEIGHT (GALV)
3"	3282-0300	5.5"	22	0.60
4"	3282-0400	5.5"	22	0.80
5"	3282-0500	5.5"	22	0.95
6"	3282-0600	5.5"	22	1.15
7"	3282-0700	5.5"	22	1.35
8"	3282-0800	5.5"	22	1.55
9"	3282-0900	5.5"	22	1.70
10"	3282-1000	5.5"	22	1.90
11"	3282-1100	5.5"	22	2.15
12"	3282-1200	5.5"	22	2.35
13"	3282-1300	5.5"	20	2.50
14"	3282-1400	5.5"	20	2.65
15"	3282-1500	5.5"	20	2.90
16"	3282-1600	5.5"	20	3.15
17"	3282-1700	5.5"	20	3.55
18"	3282-1800	5.5"	20	3.80
20"	3282-2000	5.5"	20	4.25
22"	3282-2200	5.5"	20	4.95
24"	3282-2400	5.5"	20	6.00

Hose Adapter



- Hose adapters are available in Galvanized or Stainless Steel.




**BELL MOUTH ADAPTER**

Ø (A)	Ø (B)	PART NO.	LENGTH (L)	WEIGHT (GALV)
3"	6"	3251-0300	4.5"	0.90
4"	9"	3251-0400	4.5"	1.05
5"	10"	3251-0500	4.5"	1.15
6"	12"	3251-0600	5.0"	1.85
7"	13"	3251-0700	5.0"	1.95
8"	14"	3251-0800	5.0"	2.10
9"	15"	3251-0900	5.0"	2.25
10"	16"	3251-1000	5.0"	3.00
11"	19"	3251-1100	6.0"	0.37
12"	20"	3251-1200	6.0"	4.10
13"	21"	3251-1300	6.0"	4.50
14"	22"	3251-1400	6.0"	5.75
15"	23"	3251-1500	6.0"	6.25
16"	26"	3251-1600	7.0"	7.50
17"	27"	3251-1700	7.0"	8.25
18"	28"	3251-1800	7.0"	9.50
20"	30"	3251-2000	7.0"	10.75
22"	34"	3251-2200	8.0"	12.25
24"	36"	3251-2400	8.0"	14.50

Bell Mouth Adapter



- A flared end adapter.
- Increases capture ratio of air, dust, smoke etc.
- 20 gauge



**ORDERING NOTES:**

Unless specified, 3" through 24" is QF, over 24" is flanged. Data is subject to change without notice. Stainless steel components requiring flanges will be supplied with SS flanges unless otherwise specified. Stainless steel components are manufactured with NO.304 SS. [Prices for SS 316 = SS 304 X 1.25] Adding a SS after standard part numbers specifies a SS part. For special parts or items to be custom manufactured call for quotation.

WWW.DUCTMONKEY.NET • 951-739-9593