

**BEAM CLAMP
PIPE HANGER HJ
NITRILE GASKET
NEOPRENE O-RING**



QUICK-FIT



THE WORLD'S FASTEST DUCTING

BEAM CLAMP

Ø	PART NO.	WEIGHT
3/4"	3269-0100	0.30



- Speed up connection of pipe bracing to building steel members.

PIPE HANGER HJ

Ø	PART NO.	WEIGHT (GALV)
3"	3265-0300-1HJ	0.45
4"	3265-0400-1HJ	0.55
5"	3265-0500-1HJ	0.65
6"	3265-0600-1HJ	0.75
7"	3265-0700-1HJ	0.85
8"	3265-0800-1HJ	0.95
9"	3265-0900-1HJ	1.05
10"	3265-1000-1HJ	1.15
11"	3265-1100-1HJ	1.30
12"	3265-1200-1HJ	1.45
13"	3265-1300-1HJ	1.60
14"	3265-1400-1HJ	1.75
15"	3265-1500-1HJ	1.90
16"	3265-1600-1HJ	2.20
17"	3265-1700-1HJ	2.50
18"	3265-1800-1HJ	2.85
20"	3265-2000-1HJ	3.40
22"	3265-2200-1HJ	4.10
24"	3265-2400-1HJ	5.00



- 3"-24" made from galvanized steel 14 GA.
- Clearance hole 7/16".
- Bolts are supplied with hanger.



NITRILE GASKET *

Ø	PART NO.	WEIGHT
3"	3190-0300	0.01
4"	3190-0400	0.02
5"	3190-0500	0.03
6"	3190-0600	0.04
7"	3190-0700	0.08
8"	3190-0800	0.09
9"	3190-0900	0.10
10"	3190-1000	0.11
11"	3190-1100	0.17
12"	3190-1200	0.17
13"	3190-1300	0.22
14"	3190-1400	0.23
15"	3190-1500	0.25
16"	3190-1600	0.26
17"	3190-1700	0.27
18"	3190-1800	0.28
20"	3190-2000	0.29
22"	3190-2200	0.31
24"	3190-2400	0.36




- General purpose oil resistant polymer.
- Performs well in many oil, water and hydraulic fluid applications.
- Should not be used with solvents such as acetone, MEK, ozone, chlorinated hydrocarbons, and nitro hydrocarbons.
- Temp range: -50°F to 256°F.

Classification: 1. ASTM D-1056-67.....SBW42
2. ASTM D-1056-00.....252
Suffix Requirements.....B2,C1,F2,M

NEOPRENE O-RING *

Ø	PART NO.	WEIGHT
4"	3191-0400	0.01
5"	3191-0500	0.02
6"	3191-0600	0.03
7"	3191-0700	0.04
8"	3191-0800	0.08
9"	3191-0900	0.09
10"	3191-1000	0.10
11"	3191-1100	0.11
12"	3191-1200	0.17



- Performs well with many oils and chemicals.
- Temp range: -50°F to 200°F.
- Can't be damaged by flexing and twisting.
- These materials work in conjunction with Nordfab's standard O-ring. IT DOES NOT REPLACE IT.

Classification: 1. ASTM D-1056-68.....SCE41

* NORDFAB can't guarantee that these materials will work on every application. Please see above for manufacturer's classifications. When ordering for mist application specify fully welded.

ORDERING NOTES:

Unless specified, 3" through 24" is QF, over 24" is flanged. Data is subject to change without notice. Stainless steel components requiring flanges will be supplied with SS flanges unless otherwise specified. Stainless steel components are manufactured with NO.304 SS. [Prices for SS 316 = SS 304 X 1.25] Adding a SS after standard part numbers specifies a SS part. For special parts or items to be custom manufactured call for quotation.

WWW.DUCTMONKEY.NET • 951-739-9593