



QUICK-FIT



THE WORLD'S FASTEST DUCTING

**PIPE HANGER
GRIPPLE HANGER
PIPE BRACING**

PIPE HANGER

Ø	PART NO.	WEIGHT (GALV)
3"	3265-0300	0.40
4"	3265-0400	0.45
5"	3265-0500	0.50
6"	3265-0600	0.60
7"	3265-0700	0.65
8"	3265-0800	0.75
9"	3265-0900	0.85
10"	3265-1000	0.95
11"	3265-1100	1.00
12"	3265-1200	1.10
13"	3265-1300	1.20
14"	3265-1400	1.15
15"	3265-1500	1.30
16"	3265-1600	1.35
17"	3265-1700	1.40
18"	3265-1800	1.50
20"	3265-2000	1.80
22"	3265-2200	6.00
24"	3265-2400	6.00
26"	3265-2600	6.00
28"	3265-2800	6.00
30"	3265-3000	7.50
32"	3265-3200	8.00
34"	3265-3400	8.00
36"	3265-3600	8.80
38"	3265-3800	10.00
40"	3265-4000	10.00

Pipe Hanger




- 3"-24" made from galvanized steel 14 GA.
- Clearance hole 5/16".
- Bolts are supplied with hanger.
- Over 24 inches made from 3/16" flat bar steel.



Gripple Hanger



- Comes in length of 15 feet.
- Not available in SS.



GRIPPLE HANGER

SIZE WEIGHT	PART NO.	WEIGHT (GALV)
Up to 22lbs	3266-1500-022LBS	0.05
Up to 100lbs	3266-1500-100LBS	0.10
Up to 200lbs	3266-1500-200LBS	0.75
Up to 495lbs	3266-1500-495LBS	1.10
Up to 715lbs	3266-1500-715LBS	1.20

PIPE BRACING

Ø	PART NO.	WEIGHT
1/2"	3268-0100	2.00

Pipe Bracing



- Galvanized.
- Supplied in standard length of 10 feet.
- Cut to desired length - flatten ends - drill one end with 3/8" bit - connect this end to pipe hanger and clamp or bolt other end to suspension point.
- NOT Flattened or Drilled.

ORDERING NOTES:

Unless specified, 3" through 24" is QF, over 24" is flanged. Data is subject to change without notice. Stainless steel components requiring flanges will be supplied with SS flanges unless otherwise specified. Stainless steel components are manufactured with NO.304 SS. [Prices for SS 316 = SS 304 X 1.25] Adding a SS after standard part numbers specifies a SS part. For special parts or items to be custom manufactured call for quotation.

WWW.DUCTMONKEY.NET • 951-739-9593