



QUICK-FIT



THE WORLD'S FASTEST DUCTING

RUBBER HOSE

Ø	PART NO.	WEIGHT
1"	3280-0100	0.14
1.5"	3280-1500	0.17
2"	3280-0200	0.24
2.5"	3280-2500	0.27
3"	3280-0300	0.34
3.5"	3280-3500	0.39
4"	3280-0400	0.50
5"	3280-0500	0.64
5.5"	3280-5500	0.71
6"	3280-0600	0.91
7"	3280-0700	1.00
8"	3280-0800	1.04
9"	3280-0900	1.20
10"	3280-1000	1.60
12"	3280-1200	2.00
14"	3280-1400	2.40
16"	3280-1600	2.80
18"	3280-1800	3.60
20"	3280-2000	4.00
22"	3280-2200	5.00
24"	3280-2400	6.00

Rubber Hose



PART NO. 3280

- Flexible rubber hose with steel coil.
- Order hose clamps separate.
- "Clear" "FDA" hose is also available upon request.
- Sold by the foot in 5' increments.



RIGID FLEX STEEL HOSE

Ø	PART NO.	WEIGHT
1.5"	3281-1500	1.00
2"	3281-0200	1.30
2.5"	3281-2500	1.60
3"	3281-0300	2.00
3.5"	3281-3500	2.30
4"	3281-0400	2.60
5"	3281-0500	3.00
6"	3281-0600	3.60
7"	3281-0700	4.00
8"	3281-0800	4.60
9"	3281-0900	5.30
10"	3281-1000	5.90
12"	3281-1200	7.00
14"	3281-1400	8.10

Rigid Flex Steel Hose



PART NO. 3281

- Flexible rigid steel hose for higher temperature or abrasive material.
- Available in Galvanized or Stainless Steel.
- Sold by the foot in 5' increments.

ULTRA FLEX STEEL HOSE

Ø	PART NO.	WEIGHT (GALV)
3"	3283-0300	1.00
4"	3283-0400	1.60
5"	3283-0500	2.18
6"	3283-0600	3.75
7"	3283-0700	5.08
8"	3283-0800	5.80

Ultra Flex Steel Hose



PART NO. 3283


- Special flex-steel hose.
- Available in Galvanized or Stainless Steel.
- Sold by the foot in 5' increments.

ORDERING NOTES:

Unless specified, 3" through 24" is QF, over 24" is flanged. Data is subject to change without notice. Stainless steel components requiring flanges will be supplied with SS flanges unless otherwise specified. Stainless steel components are manufactured with NO.304 SS. [Prices for SS 316 = SS 304 X 1.25] Adding a SS after standard part numbers specifies a SS part. For special parts or items to be custom manufactured call for quotation.

WWW.DUCTMONKEY.NET • 951-739-9593

RIGID METAL FLEX HOSE



Part # 3281-XX00

Inside Dia. (Inches)	Appox. Outside Dia. (Inches)	Min. CLR Bend Radius	Appox. Weight Per Foot (LBS)
1 1/2	1 3/4	5.5	0.85
2	2 1/4	6.5	1.15
2 1/2	2 3/4	8.5	1.44
3	3 1/4	10.5	1.73
3 1/2	3 3/4	12.5	2.01
4	4 1/4	13.5	2.30
5	5	16.5	2.86

MEDIUM-HEAVY GALVANIZED OR STAINLESS

Inside Dia. (Inches)	Appox. Outside Dia. (Inches)	Min. CLR Bend Radius	Appox. Weight Per Foot (LBS)
6	6 1/4	21.5	3.45
7	7 1/4	24.0	4.03
8	8 1/4	27.5	4.60
9	9 1/4	29.5	5.18
10	10 1/4	31.5	5.75
12	12 1/4	38.0	6.90
14	14 1/4	42.5	8.05

.017- .020 Strip Thickness

ULTRA FLEX METAL HOSE

Part # 3283-XX00

Inside Dia. (Inches)	Min. CLR Bend Radius	Appox. Weight Per Foot (LBS)
3	8.13	1.04
4	9.38	1.20
5	12.38	1.68

Manufactured in sizes ranging from 3" dia thru 8" dia of stainless steel or galvanized. Some Applications would include Air Handling, and Dust Collection.

Inside Dia. (Inches)	Min. CLR Bend Radius	Appox. Weight Per Foot (LBS)
6	15.63	2.00
7	16.50	2.80
8	19.75	3.20

Square Lock: ID Tolerance: +1/4" , - 0
 Specification: 3"-6" manufactured out of .019 material
 7"-8" manufactured out of .024 material

RIGID AND ULTRA FLEX STEEL HOSE CONFIGURATIONS


Steel Flex Hose With Raw Ends (Standard)




Steel Flex Hose With Q-F Ends (Custom)



Steel Flex Hose With Flange Ends (Custom)



Steel Flex Hose With Raw Pipe Ends (Custom)



NOTE: When ordering steel hose, you have the option of having the hose fitted with several different style end fittings in any number of combinations. Raw hose is priced per foot, and sold only in 5 Ft. increments. Contact your sales rep for pricing on specific lengths and end fittings.