


### RIGID METAL FLEX HOSE



Part # 3281-XX00

Inside Dia. (Inches)	Appox. Outside Dia. (Inches)	Min. CLR Bend Radius	Appox. Weight Per Foot (LBS)
1 1/2	1 3/4	5.5	0.85
2	2 1/4	6.5	1.15
2 1/2	2 3/4	8.5	1.44
3	3 1/4	10.5	1.73
3 1/2	3 3/4	12.5	2.01
4	4 1/4	13.5	2.30
5	5	16.5	2.86

MEDIUM-HEAVY GALVANIZED OR STAINLESS

Inside Dia. (Inches)	Appox. Outside Dia. (Inches)	Min. CLR Bend Radius	Appox. Weight Per Foot (LBS)
6	6 1/4	21.5	3.45
7	7 1/4	24.0	4.03
8	8 1/4	27.5	4.60
9	9 1/4	29.5	5.18
10	10 1/4	31.5	5.75
12	12 1/4	38.0	6.90
14	14 1/4	42.5	8.05

.017- .020 Strip Thickness

### ULTRA FLEX METAL HOSE

Part # 3283-XX00

Inside Dia. (Inches)	Min. CLR Bend Radius	Appox. Weight Per Foot (LBS)
3	8.13	1.04
4	9.38	1.20
5	12.38	1.68

Manufactured in sizes ranging from 3" dia thru 8" dia of stainless steel or galvanized. Some Applications would include Air Handling, and Dust Collection.

Inside Dia. (Inches)	Min. CLR Bend Radius	Appox. Weight Per Foot (LBS)
6	15.63	2.00
7	16.50	2.80
8	19.75	3.20

Square Lock: ID Tolerance: +1/4" , - 0  
 Specification: 3"-6" manufactured out of .019 material  
 7"-8" manufactured out of .024 material

### RIGID AND ULTRA FLEX STEEL HOSE CONFIGURATIONS


Steel Flex Hose With Raw Ends (Standard)



Steel Flex Hose With Q-F Ends (Custom)



Steel Flex Hose With Flange Ends (Custom)




Steel Flex Hose With Raw Pipe Ends (Custom)



NOTE: When ordering steel hose, you have the option of having the hose fitted with several different style end fittings in any number of combinations. Raw hose is priced per foot, and sold only in 5 Ft. increments. Contact your sales rep for pricing on specific lengths and end fittings.

## RIGID METAL FLEX HOSE



Part # 3281-XX00

Inside Dia. (Inches)	Appox. Outside Dia. (Inches)	Min. CLR Bend Radius	Appox. Weight Per Foot (LBS)
1 1/2	1 3/4	5.5	0.85
2	2 1/4	6.5	1.15
2 1/2	2 3/4	8.5	1.44
3	3 1/4	10.5	1.73
3 1/2	3 3/4	12.5	2.01
4	4 1/4	13.5	2.30
5	5	16.5	2.86

MEDIUM-HEAVY GALVANIZED OR STAINLESS

Inside Dia. (Inches)	Appox. Outside Dia. (Inches)	Min. CLR Bend Radius	Appox. Weight Per Foot (LBS)
6	6 1/4	21.5	3.45
7	7 1/4	24.0	4.03
8	8 1/4	27.5	4.60
9	9 1/4	29.5	5.18
10	10 1/4	31.5	5.75
12	12 1/4	38.0	6.90
14	14 1/4	42.5	8.05

.017- .020 Strip Thickness

## ULTRA FLEX METAL HOSE

Part # 3283-XX00

Inside Dia. (Inches)	Min. CLR Bend Radius	Appox. Weight Per Foot (LBS)
3	8.13	1.04
4	9.38	1.20
5	12.38	1.68

Manufactured in sizes ranging from 3" dia thru 8" dia of stainless steel or galvanized. Some Applications would include Air Handling, and Dust Collection.

Inside Dia. (Inches)	Min. CLR Bend Radius	Appox. Weight Per Foot (LBS)
6	15.63	2.00
7	16.50	2.80
8	19.75	3.20

Square Lock: ID Tolerance: +1/4" , - 0  
 Specification: 3"-6" manufactured out of .019 material  
 7"-8" manufactured out of .024 material

## RIGID AND ULTRA FLEX STEEL HOSE CONFIGURATIONS


Steel Flex Hose With Raw Ends (Standard)




Steel Flex Hose With Q-F Ends (Custom)



Steel Flex Hose With Flange Ends (Custom)



Steel Flex Hose With Raw Pipe Ends (Custom)



NOTE: When ordering steel hose, you have the option of having the hose fitted with several different style end fittings in any number of combinations. Raw hose is priced per foot, and sold only in 5 Ft. increments. Contact your sales rep for pricing on specific lengths and end fittings.