



QUICK-FIT



THE WORLD'S FASTEST DUCTING

HOSE

RUBBER HOSE

Ø	PART NO.	WEIGHT
1"	3280-0100	0.14
1.5"	3280-1500	0.17
2"	3280-0200	0.24
2.5"	3280-2500	0.27
3"	3280-0300	0.34
3.5"	3280-3500	0.39
4"	3280-0400	0.50
5"	3280-0500	0.64
5.5"	3280-5500	0.71
6"	3280-0600	0.91
7"	3280-0700	1.00
8"	3280-0800	1.04
9"	3280-0900	1.20
10"	3280-1000	1.60
12"	3280-1200	2.00
14"	3280-1400	2.40
16"	3280-1600	2.80
18"	3280-1800	3.60
20"	3280-2000	4.00
22"	3280-2200	5.00
24"	3280-2400	6.00

Rubber Hose



PART NO. 3280

- Flexible rubber hose with steel coil.
- Order hose clamps separate.
- "Clear" "FDA" hose is also available upon request.
- Sold by the foot in 5' increments.



RIGID FLEX STEEL HOSE

Ø	PART NO.	WEIGHT
1.5"	3281-1500	1.00
2"	3281-0200	1.30
2.5"	3281-2500	1.60
3"	3281-0300	2.00
3.5"	3281-3500	2.30
4"	3281-0400	2.60
5"	3281-0500	3.00
6"	3281-0600	3.60
7"	3281-0700	4.00
8"	3281-0800	4.60
9"	3281-0900	5.30
10"	3281-1000	5.90
12"	3281-1200	7.00
14"	3281-1400	8.10

Rigid Flex Steel Hose



PART NO. 3281

- Flexible rigid steel hose for higher temperature or abrasive material.
- Available in Galvanized or Stainless Steel.
- Sold by the foot in 5' increments.

ULTRA FLEX STEEL HOSE

Ø	PART NO.	WEIGHT (GALV)
3"	3283-0300	1.00
4"	3283-0400	1.60
5"	3283-0500	2.18
6"	3283-0600	3.75
7"	3283-0700	5.08
8"	3283-0800	5.80

Ultra Flex Steel Hose



PART NO. 3283

- Special flex-steel hose.
- Available in Galvanized or Stainless Steel.
- Sold by the foot in 5' increments.

ORDERING NOTES:

Unless specified, 3" through 24" is QF, over 24" is flanged. Data is subject to change without notice. Stainless steel components requiring flanges will be supplied with SS flanges unless otherwise specified. Stainless steel components are manufactured with NO.304 SS. [Prices for SS 316 = SS 304 X 1.25] Adding a SS after standard part numbers specifies a SS part. For special parts or items to be custom manufactured call for quotation.

WWW.DUCTMONKEY.NET • 951-739-9593


NORDFAB
QUICK-FIT 
THE WORLD'S FASTEST DUCTING

RUBBER FLEXIBLE HOSE

Why Buy RFH Hose:

- Wider Temperature Range
- Superior Chemical Resistance
- Versatility
- Better Abrasion Resistance
- Better UV, Moisture and Weathering Resistance
- Outstanding Flex Resistance
- Will Not Set to The Shape of the Box When Packed
- Better Looking Product
- No Cement
- Air Tight

RFH




**General Purpose
 Part # 3280-XX00**

Specifications
 Temperature Range: -60 F. to 275 F.
 (intermittent to 300 F.)
 Standard Color: Black
 Standard Length: 5' increments with 5' min
 Sizes: 1", 1.5", 2", 2.5", 3", 3.5", 4", 5", 5.5", 6",
 7", 8", 9", 10", 11", 12", 13", 14", 16", 18", 20", 24"

Description: Constructed of thermoplastic rubber and reinforced with wire helix, RFH is the most versatile general-purpose hose available today. No cements, solvents, chemicals, adhesives or glues are used in the manufacturing process of RFH. RFH has superior chemical resistance and is capable of handling fumes as tough as Methyl Ethyl Ketone, sulfuric acid or toluene. RFH is manufactured in standard black. Please consult us for minimums and prices for other lengths and on non-standard diameters, including metric sizes from 51mm to 500mm.

CVD




**General Purpose, Economical
 Part # 3280-XX00-700000**

Specifications:
 Temperature Range: -20 F to 180 F
 Standard Color: Clear
 Standard Length: 5' increments with 5' min
 Sizes: 1", 1.5", 2", 2.5", 3", 3.5", 4", 5", 5.5", 6",
 7", 8", 10", 12", 14, 16", 18"

Description: Constructed of polyvinylchloride and reinforced with steel wire, CVD is an excellent choice for many industrial and food service applications. CVD is an economical alternative to most ducts and sacrifices nothing in performance. CVD is an excellent choice for applications involving fume removal dust collection, ventilation and other more rigorous industrial requirements. Material used in clear hose is FDA acceptable.

UFD



**Tough Or Severe Service
 Applications Custom Part Can
 Be Ordered And Shipped Direct.**

Specifications:
 Temperature Range: -65 F to 200 F
 Standard Color: Clear or Black
 Standard Length: 5' increments with 5' min
 Sizes: 1", 1.5", 2", 2.5", 3", 4" 5" 6" 7" 8" 10"
 12", 14", 16", 18"

Description: Constructed of thermoplastic urethane and reinforced with a wire helix, UFD offers superior abrasion resistance. UFD is the answer for those who want a lightweight, flexible hose which can handle much abrasion. UFD can be used in numerous applications such as leaf loading, chip handling, dust collection, etc. The superior transparency of the clear UFD allows users to locate blockages. This hose is suitable for severe service applications including vacuum and high abrasion. Material used in clear hose is FDA acceptable.