



QUICK-FIT



THE WORLD'S FASTEST DUCTING

QF IN-CUT QF TAP-IN


IN CUT

Ø	PART NO.	ENDS	GAUGE		WEIGHT (GALV)
			GAL.	SS	
3"	3223-03XX	QF	22	22	1.25
4"	3223-04XX	QF	22	22	1.48
5"	3223-05XX	QF	22	22	2.15
6"	3223-06XX	QF	22	22	2.84
7"	3223-07XX	QF	22	22	3.53
8"	3223-08XX	QF	22	22	4.48
9"	3223-09XX	QF	22	22	5.38
10"	3223-10XX	QF	22	22	6.47
11"	3223-11XX	QF	22	22	7.82
12"	3223-12XX	QF	22	22	8.77
13"	3223-13XX	QF	20	20	11.23
14"	3223-14XX	QF	20	20	13.68
15"	3223-15XX	QF	20	20	15.79
16"	3223-16XX	QF	20	20	17.20
17"	3223-17XX	QF	20	20	19.26
18"	3223-18XX	QF	20	20	21.29
20"	3223-20XX	QF	20	20	25.58
22"	3223-22XX	QF	20	20	30.47
24"	3223-24XX	QF	20	20	35.36
26"	3223-26XX	FLANGE	18	18	40.28
28"	3223-28XX	FLANGE	18	18	45.01
30"	3223-30XX	FLANGE	18	18	56.53
32"	3223-32XX	FLANGE	18	18	62.97
34"	3223-34XX	FLANGE	18	18	67.42
36"	3223-36XX	FLANGE	18	18	71.38
38"	3223-38XX	FLANGE	18	18	76.74
40"	3223-40XX	FLANGE	18	18	81.41

In Cut



- Priced by 'B' diameter.
- Specify 'A' and 'B' diameter and end treatment.
- Standard 30° Optional 45°.
- Incut used to cut into existing lines to begin QF system.




TAP IN

Ø	PART NO.	ENDS	GAUGE		WEIGHT (GALV)
			GAL.	SS	
3"	3224-03XX	QF	22	22	0.45
4"	3224-04XX	QF	22	22	0.62
5"	3224-05XX	QF	22	22	0.84
6"	3224-06XX	QF	22	22	1.12
7"	3224-07XX	QF	22	22	1.35
8"	3224-08XX	QF	22	22	1.63
9"	3224-09XX	QF	22	22	1.94
10"	3224-10XX	QF	22	22	2.26
11"	3224-11XX	QF	22	22	2.47
12"	3224-12XX	QF	22	22	2.92
13"	3224-13XX	QF	20	20	3.30
14"	3224-14XX	QF	20	20	4.41
15"	3224-15XX	QF	20	20	5.10
16"	3224-16XX	QF	20	20	5.60
17"	3224-17XX	QF	20	20	6.10
18"	3224-18XX	QF	20	20	6.74
20"	3224-20XX	QF	20	20	7.68
22"	3224-22XX	QF	20	20	8.94
24"	3224-24XX	QF	20	20	11.25
26"	3224-26XX	FLANGE	18	18	35.28
28"	3224-28XX	FLANGE	18	18	40.00
30"	3224-30XX	FLANGE	18	18	51.53
32"	3224-32XX	FLANGE	18	18	57.97
34"	3224-34XX	FLANGE	18	18	62.42
36"	3224-36XX	FLANGE	18	18	66.38
38"	3224-38XX	FLANGE	18	18	71.74
40"	3224-40XX	FLANGE	18	18	79.41

Tap In



- Priced by 'B' diameter.
- Specify 'A' and 'B' diameter and end treatment.
- Tap In used to cut into existing lines to begin QF system.



ORDERING NOTES:

Unless specified, 3" through 24" is QF, over 24" is flanged. Data is subject to change without notice. Stainless steel components requiring flanges will be supplied with SS flanges unless otherwise specified. Stainless steel components are manufactured with NO.304 SS. [Prices for SS 316 = SS 304 X 1.25] Adding a SS after standard part numbers specifies a SS part. For special parts or items to be custom manufactured call for quotation.

WWW.DUCTMONKEY.NET • 951-739-9593